



کاتالوگ محصولات هیکان

زمستان ۱۴۰۴



WWW.HIKANIRAN.COM



AHD CAMERA



HK-AHC-BW2760DE

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/3DNR
WARMLIGHT
18.5CM*7CM*6CM/DC12V



HK-AHC-BW2755DE

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
FLC/BLC/2DNR/3DNR
WARMLIGHT
18.5CM*7CM*7CM/DC12V



HK-AHC-BW2732B

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/FLC/BLC/2DNR/3DNR
WARMLIGHT
16CM*7CM*6CM/DC12V



HK-AHC-HBW2765B

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/FLC/BLC/2DNR/3DNR
WARMLIGHT
19.5CM*7CM*6.8CM/DC12V



HK-AHC-DW2706B

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/FLC/BLC/2DNR/3DNR
WARMLIGHT
10.5CM*10.5CM*6CM/DC12V



HK-AHC-BW2745EA

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/AUDIO
WARMLIGHT
16CM*6.5CM*6CM/DC12V



HK-AHC-HBW2755EA

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/3DNR/ANTIFlicker
WARMLIGHT
18.5CM*7CM*7CM/DC12V



WWW.HIKANIRAN.COM



AHD CAMERA



(BIG CASE)

HK-AHC-BW2865EA

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/BIG CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/AUDIO
WARMLIGHT
31CM*9CM*8CM/DC12V



HK-AHC-DW2706EA

RESOLUTION : 2 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/AUDIO
WARMLIGHT
10.5CM*10.5CM*6CM/DC12V



HK-AHC-BW5732H

RESOLUTION : 5 MEGAPIXEL 20FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/FLC/BLC/2DNR
WARMLIGHT
16CM*7CM*6CM/DC12V



HK-AHC-HBW5755H

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
ANTIFLICKER/BLC/2DNR
WARMLIGHT
18.5CM*7CM*7CM/DC12V



(BIG CASE)

HK-AHC-BW5860H

RESOLUTION : 5 MEGAPIXEL 20FPS
LENS : FIXED 3.6MM
METAL/BIG CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/FLC/BLC/2DNR
WARMLIGHT
31CM*9CM*8CM/DC12V



HK-AHC-DW5706H

RESOLUTION : 5 MEGAPIXEL 20FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/FLC/BLC/2DNR
WARMLIGHT
10.5CM*10.5CM*6CM/DC12V



HK-AHC-BW5745RA

RESOLUTION : 5 MEGAPIXEL 20FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/DNR/AUDIO
WARMLIGHT
16CM*6.5CM*6CM/DC12V



WWW.HIKANIRAN.COM



AHD CAMERA



HK-AHC-HBW5765RA

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
ANTIFLICKER/BLC/2DNR/AUDIO
WARMLIGHT
19.5CM*7CM*6.8CM/DC12V



(BIG CASE)

HK-AHC-BW5860RA

RESOLUTION : 5 MEGAPIXEL 20FPS
LENS : FIXED 3.6MM
METAL/BIG CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/AUDIO
WARMLIGHT
31CM*9CM*8CM/DC12V



HK-AHC-DW5706RA

RESOLUTION : 5 MEGAPIXEL 20FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
OSD MENU BY UTC(4 IN 1)
DWDR/BLC/2DNR/AUDIO
WARMLIGHT
10.5CM*10.5CM*6CM/DC12V



WWW.HIKANIRAN.COM



IP CAMERA



(BIG CASE)

HK-IPC-BW2860NAPL

RESOLUTION : 2 MEGAPIXEL 60FPS
LENS : FIXED 12MM
METAL/BIG CASE/IP67
WARMLIGHT/AUDIO/3DNR
ANTI FUG/WDR/H265/POE/LPC
HUMAN-MOTION DETECTION
30CM*9CM*8.5CM/DC12V



HK-IPC-BW5735XAP

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
WARMLIGHT/AUDIO
ANTIFLICKE/WDR/H265/POE
HUMAN-MOTION DETECTION
19CM*7CM*6.5CM/DC12V



HK-IPC-BW5732XAP

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
WARMLIGHT/AUDIO
ANTIFLICKE/WDR/H265/POE
HUMAN-MOTION DETECTION
16CM*7CM*6CM/DC12V



(BIG CASE)

HK-IPC-BW5860XAP

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/BIG CASE/IP67
WARMLIGHT/AUDIO
ANTIFLICKE/WDR/H265/POE
HUMAN-MOTION DETECTION
30CM*9CM*8.5CM/DC12V



HK-IPC-DW5706XAP

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
WARMLIGHT/AUDIO
ANTIFLICKE/WDR/H265/POE
HUMAN-MOTION DETECTION
10.5CM*10.5CM*6CM/DC12V



HK-IPC-HBW5790SAP

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67/AUDIO/LIGHT ALARM
WARMLIGHT/H265+/POE/ANTIFLICKE/3DNR/P2P
DEFOGGING/INTRUSION DETECTION
OFF DUTY DETECTION/TRIPWIRE CROSSING DETECTION
PASSENGER FLOW STATISTICS
17CM*6.7CM*7CM/DC12V



HK-IPC-BW5745SAP-R

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : FIXED 3.6MM/ALARM OUT/LIGHT ALARM
METAL/MEDIUM CASE/IP67/AUDIO/H265+/POE
WARMLIGHT/ANTIFLICKE/3DNR/P2P
DEFOGGING/PASSENGER FLOW STATISTICS
OFF DUTY DETECTION/INTRUSION DETECTION
TRIPWIRE CROSSING DETECTION
16.5CM*6.5CM*6CM/DC12V



WWW.HIKANIRAN.COM



IP CAMERA



HK-IPC-HBDW5765SAP

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM/WARMLIGHT/DARKLIGHT
 METAL/MEDIUM CASE/IP67/AUDIO/LIGHT ALARM
 ANTIFLICKER/P2P/3DNR/H265+/POE
 OFF DUTY DETECTION/PASSENGER FLOW STATISTICS
 DEFOGGING/TRIP WIRE CROSSING DETECTION
 INTRUSION DETECTION
 19.5CM*7CM*6.8CM/DC12V



HK-IPC-HBW6765SAP

RESOLUTION : 6 MEGAPIXEL 20FPS
 LENS : FIXED 3.6MM/WARMLIGHT/LIGHT ALARM
 METAL/MEDIUM CASE/IP67/AUDIO
 P2P/DEFOGGING/3DNR/H265+/POE/ANTIFLICKER
 PASSENGER FLOW STATISTICS/OFF DUTY DETECTION
 TRIP WIRE CROSSING DETECTION
 INTRUSION DETECTION
 19.5CM*7CM*6.8CM/DC12V



HK-IPC-HBW8765SAP

RESOLUTION : 8 MEGAPIXEL 20FPS
 LENS : FIXED 3.6MM/WARMLIGHT/LIGHT ALARM
 METAL/MEDIUM CASE/IP67/AUDIO
 P2P/3DNR/H265+/POE/ANTIFLICKER/DEFOGGING
 OFF DUTY DETECTION/PASSENGER FLOW STATISTICS
 TRIP WIRE CROSSING DETECTION
 INTRUSION DETECTION
 19.5CM*7CM*6.8CM/DC12V



HK-IPC-BW8890SAPZ5

RESOLUTION : 8 MEGAPIXEL 20FPS
 LENS : MOTORIZED 2.8MM-12MM/WARMLIGHT
 METAL/BIG CASE/IP67/AUDIO/LIGHT ALARM
 P2P/3DNR/H265+/POE/ANTIFLICKER/DEFOGGING
 PASSENGER FLOW STATISTICS/OFF DUTY DETECTION
 TRIP WIRE CROSSING DETECTION
 INTRUSION DETECTION
 23CM*7.8CM*7.5CM/DC12V



HK-IPC-BW5710SA2PSDF-R

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM/WARMLIGHT
 METAL/MEDIUM CASE/IP67
 AUDIO(IN-OUT)/SD SUPPORT
 3DNR/H265/ALARM OUT/FD/FR/POE
 DEFENSER AREA/LIGHT ALARM
 FACE-HUMAN-MOTION DETECTION
 19CM*7CM*7CM/DC12V



HK-IPC-BW5860SA2PSDL-R

RESOLUTION : 5 MEGAPIXEL 25 FPS
 LENS : FIXED 12MM/WARMLIGHT
 METAL/BIG CASE/IP67
 AUDIO(IN-OUT)/SD SUPPORT
 3DNR/H265/ALARM OUT/LPR/POE
 DEFENSER AREA/LIGHT ALARM
 VEHICLE-HUMAN-MOTION DETECTION
 30CM*9CM*8.5CM/DC12V



HK-IPC-BPW5730SAPF-R

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM
 METAL/MEDIUM CASE/IP67
 WARMLIGHT/AUDIO
 3DNR/H265/ALARM OUT/FD/FR/ELS/POE
 DEFENSER AREA/EMERGENCY LIGHT ALARM
 FACE-HUMAN-MOTION DETECTION
 18.5CM*7CM*6CM/DC12V



WWW.HIKANIRAN.COM



IP CAMERA



HK-IPC-DW5703SA2PF-R

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM/WARMLIGHT/H265/ALARM OUT
 PLASTIC/MEDIUM CASE/IP67/AUDIO(IN-OUT)
 P2P/POE/ANTIFLICKER/FD/FR/BLC/3DNR
 DEFOGGING/PASSENGER FLOW STATISTICS
 TRIP WIRE CROSSING DETECTION
 TRFFIC FLOW STATISTICS
 INTRUSION DETECTION/OFF DUTY DETECTION
 10.5CM*10.5CM*8.5CM/DC12V



HK-IPC-BW5735UAP

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM
 METAL/MEDIUM CASE/IP67
 BLC/HLC/HDR/2DNR/H265+/WDR/POE
 ANTIFLICKER/DEFOGGING/WARMLIGHT/AUDIO
 INTELLIGENT
 HUMAN-VEHICLE DETECTION
 19CM*7CM*6.5CM/DC12V



HK-IPC-BU5732UAP

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM
 METAL/MEDIUM CASE/IP67
 BLC/HLC/HDR/2DNR/H265+/WDR/POE
 DEFOGGING/ANTIFLICKER/DUALLIGHT/AUDIO
 INTELLIGENT
 HUMAN-VEHICLE DETECTION
 16CM*7CM*6CM/DC12V



HK-IPC-HBDW5765UAP

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM/WARMLIGHT/DARKLIGHT
 METAL/MEDIUM CASE/IP67/AUDIO
 P2P/3DNR/H265+/POE/ANTIFLICKER/DEFOGGING
 PASSENGER FLOW STATISTICS
 TRIP WIRE CROSSING DETECTION
 INTRUSION DETECTION//OFF DUTY DETECTION
 19.5CM*7CM*6.8CM/DC12V



(BIG CASE)

HK-IPC-BW5860UAP

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM
 METAL/BIG CASE/IP67
 BLC/HLC/HDRWDR/2DNR/H265+/POE
 DEFOGGING/ANTIFLICKER/WARMLIGHT/AUDIO
 INTELLIGENT
 HUMAN-VEHICLE DETECTION
 30CM*9CM*8.5CM/DC12V



HK-IPC-DW5706UAP

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : FIXED 3.6MM
 METAL/MEDIUM CASE/IP67
 BLC/HLC/HDR/2DNRWDR/H265+/POE
 DEFOGGING/ANTIFLICKER/WARMLIGHT/AUDIO
 INTELLIGENT
 HUMAN-VEHICLE DETECTION
 10.5CM*10.5CM*6CM/DC12V



(BIG CASE)

HK-IPC-BW5895UAPZ4

RESOLUTION : 5 MEGAPIXEL 25FPS
 LENS : MOTORIZED 2.8MM-12MM/WARMLIGHT
 METAL/BIG CASE/IP67/AUDIO
 P2P/3DNR/H265+/POE/ANTIFLICKER/DEFOGGING
 PASSENGER FLOW STATISTICS
 TRIP WIRE CROSSING DETECTION
 INTRUSION DETECTION/OFF DUTY DETECTION
 23CM*7.8CM*7.5CM/DC12V



WWW.HIKANIRAN.COM



IP CAMERA



(BIG CASE)

HK-IPC-BW5885UAPZ10

RESOLUTION : 5 MEGAPIXEL 25FPS
LENS : MOTORIZED 5MM-50MM/WARMLIGHT/AUDIO
METAL/BIG CASE/IP67/3DNR/H265+/POE
ANTIFLICKER/DEFOGGING
PASSENGER FLOW STATISTICS/OFF DUTY DETECTION
TRIP WIRE CROSSING DETECTION
INTRUSION DETECTION
26.3CM*8.5CM*8.5CM/DC12V



HK-IPC-BW8745KAP

RESOLUTION : 8 MEGAPIXEL 20FPS(4K)
2MEGAPIXEL 60FPS/LENS : FIXED 3.6MM
METAL/MEDIUM CASE/IP67
BLC/HLC/HDR/2DNR/3DNR/WDR/H265+/POE
DEFOGGING/WARMLIGHT/AUDIO
ANTIFLICKER
HUMAN VEHICLE DETECTION
16.5CM*6.5CM*6CM/DC12V



(BIG CASE)

HK-IPC-BW8865KAP

RESOLUTION : 8 MEGAPIXEL 20FPS(4K)
2MEGAPIXEL 60FPS/LENS : FIXED 3.6MM
METAL/BIG CASE/IP67
BLC/HLC/HDR/2DNR/WDR/3DNR/H265+/POE
DEFOGGING/WARMLIGHT/AUDIO
ANTIFLICKER
HUMAN VEHICLE DETECTION
31CM*9CM*8CM/DC12V



WWW.HIKANIRAN.COM



WIRELESS CAMERA



HK-IPC-K2100CWA2SDZ

RESOLUTION : 2 MEGAPIXEL/WIFI
LENS : FIXED 3.6MM
SD SUPPORT (UP TO 128GB)
PLASTIC/MEDIUM CASE
IOS/ANDROID(TSEYE)
MOTION DETECTION
AUDIO(IN-OUT)/PTZ
7.5CM*7.5CM*11CM



HK-IPC-KU2200CWA2SDZ

RESOLUTION : 2 MEGAPIXEL/WIFI
LENS : FIXED 3.6MM/DUAL LIGHT
SD SUPPORT (UP TO 128GB)
PLASTIC/MEDIUM CASE
IOS/ANDROID(TSEYE)
MOTION DETECTION
AUDIO(IN-OUT)/PTZ
6.5CM*6.5CM*15CM



WWW.HIKANIRAN.COM



EXTENDER VIDEO RECORDER



HK-XR-5104NN2AI

4CHANNEL/5MN/HDD:1 SATA PORT UP TO 6TB
 AUDIO:4CH AOC
 H265/VGA/HDMI/5 IN 1
 P2P SUPPORT IOS/ANDROID APP(HIEASY)
 PC SOFTWARE (EASY VMS)
 4CH(5MN(ANALOG),1080P(DIGITAL))/
 4CH 5M(DIGITAL)
 ALARM(MOTION/VIDEO LOSS/MASKING)
 SMART ALARM(E-FENCE/CROSSING/FLOW
 CONTROL/DEPARTURE PASSENGERS)
 DISPLAY RESOLUTION:3840*2160(4K)



HK-XR-5108NN2AI

8CHANNEL/5MN/HDD:1 SATA PORT UP TO 6TB
 AUDIO:8CH AOC
 H265/VGA/HDMI/5 IN 1
 P2P SUPPORT IOS/ANDROID APP(HIEASY)
 PC SOFTWARE (EASY VMS)
 8CH(5MN(ANALOG),1080P(DIGITAL))/
 8CH 5M(DIGITAL)
 ALARM(MOTION/VIDEO LOSS/MASKING)
 SMART ALARM(E-FENCE/CROSSING/FLOW
 CONTROL/DEPARTURE PASSENGERS)
 DISPLAY RESOLUTION:3840*2160(4K)



HK-XR-5216NN2AI

16CHANNEL/5MN/HDD:2 SATA PORT UP TO 6TB
 AUDIO:16CH AOC
 H265/VGA/HDMI/5 IN 1
 P2P SUPPORT IOS/ANDROID APP(HIEASY)
 PC SOFTWARE (EASY VMS)
 16CH(5MN(ANALOG),1080P(DIGITAL))/
 8CH 5M(DIGITAL)
 ALARM(MOTION/VIDEO LOSS/MASKING)
 SMART ALARM(E-FENCE/CROSSING/FLOW
 CONTROL/DEPARTURE PASSENGERS)
 DISPLAY RESOLUTION:3840*2160(4K)



HK-XR-8108KMA4

8CHANNEL/4K/HDD:1 SATA PORT UP TO 6TB
 AUDIO:4CH RCA/8CH AOC/H265/VGA/HDMI/5 IN 1
 P2P SUPPORT IOS/ANDROID APP(TS EYE)
 PC SOFTWARE (VMS)
 8CH(8MN(ANALOG),8M(DIGITAL))+
 2CH 8M(DIGITAL)
 ALARM(FACE/HUMAN/MOTION DETECTION
 VIDEO BLIND/VIDEO LOSS/ABNORMALITY)
 DISPLAY RESOLUTION:3840*2160(4K)



WWW.HIKANIRAN.COM



NETWORK VIDEO RECORDER



HK-NR-8110KM2AI

10 CHANNEL 8MP /HDD:1 SATA PORT UP TO 10TB
H265/VGA/HDMI/AUDIO
P2P SUPPORT IOS/ANDROID APP(HIEASY)
PC SOFTWARE (EASY VMS)
ALARM(FACE/VEHICLE MANAGMENT)
AI SEARCH(FACE/VEHICLE/BEHAVIORAL/MASK
PASSENGER FLOW/ELECTRONIC FENCE/CROSS
BOUNDARY/OFF-DUTYDETECTION/TRAFFIC FLOW)
DISPLAY RESOLUTION:3840*2160(4K)



HK-NR-8116KM2AI

16 CHANNEL 8MP /HDD:1 SATA PORT UP TO 10TB
H265/VGA/HDMI/AUDIO
P2P SUPPORT IOS/ANDROID APP(HIEASY)
PC SOFTWARE (EASY VMS)
ALARM(FACE/VEHICLE MANAGMENT)
AI SEARCH(FACE/VEHICLE/BEHAVIORAL/MASK
PASSENGER FLOW/ELECTRONIC FENCE/CROSS
BOUNDARY/OFF-DUTYDETECTION/TRAFFIC FLOW)
DISPLAY RESOLUTION:3840*2160(4K)



HK-NR-8216KMA16

16CHANNEL 8MP(4K)/32CHANNEL 5MP
HDD:2 SATA PORT UP TO 8TB
H265/VGA/HDMI/AUDIO
P2P SUPPORT IOS/ANDROID APP(TS EYE)
PC SOFTWARE (VMS)
ALARM(IVS/SMD/MOTION DETECTION
VIDEO BLIND/VIDEO LOSS/ABNORMALITY)
DISPLAY RESOLUTION:3840*2160(4K)



HK-NR-8236KM2AI

36 CHANNEL 8MP /HDD:2 SATA PORT UP TO 10TB
H265/VGA/HDMI/AUDIO
P2P SUPPORT IOS/ANDROID APP(HIEASY)
PC SOFTWARE (EASY VMS)
ALARM(FACE/VEHICLE MANAGMENT)
AI SEARCH(FACE/VEHICLE/BEHAVIORAL/MASK
PASSENGER FLOW/ELECTRONIC FENCE/CROSS
BOUNDARY/OFF-DUTYDETECTION/TRAFFIC FLOW)
DISPLAY RESOLUTION:3840*2160(4K)



WWW.HIKANIRAN.COM



POWER ADAPTER



CCTV ADAPTER HIKAN

INPUT POWER : 100-240V 0.8A
INPUT AC FREQUENCY : 50HZ/60HZ
OUTPUT VOLTAGE : DC12V
OUTPUT : 2.2A-2.8A/26W-33W



WWW.HIKANIRAN.COM



NETWORK SWITCH



HK-SW-0400

Rj45 port: 4*10/100mbps
uplink port: not support sfp: not support
Bandwidth: 1 GBPS
extend: not support
network signal(transmission distance): ≤150M
working enviroment(working temperature): -10°_55°
material case: plastic
pse output: not support
power in: DC5V_0.5A
size: 85*56*22mm



HK-SW-0800

Rj45 port: 8*10/100mbps
uplink port: not support sfp: not support
Bandwidth: 1.6 GBPS
extend: not support
network signal(transmission distance): ≤150M
working enviroment(working temperature): -10°_55°
material case: metal
pse output: not support
power in: 5_12 = 500ma
size: 140*48*25mm



HK-SW-G0800

Rj45 port: 8*10/100/1000mbps
uplink port: not support sfp: not support
Bandwidth: 20 GBPS
extend: not support
network signal(transmission distance): ≤150M
working enviroment(working temperature): -10°_55°
material case: metal
pse output: not support
power in: 5_12 = 500ma
size: 140*80*25mm



HK-SW-G1600

Rj45 port: 16*10/100/1000mbps
uplink port: not support sfp: not support
Bandwidth: 52 GBPS
extend: not support
network signal(transmission distance): ≤150M
working enviroment(working temperature): -10°_55°
material case: metal
pse output: not support
power in: ac 220V
size: 270*181*45mm



HK-SW-G2400

Rj45 port: 24*10/100/1000mbps
uplink port: not support sfp: not support
Bandwidth: 52 GBPS
extend: not support
network signal(transmission distance): ≤100M
working enviroment(working temperature): -25°_40°
material case: metal
pse output: not support
power in: ac 110-240V 1/5A
size: 270*181*45mm



HK-SW-P0200-i1

Poe Rj45 port: 2*10/100/1000mbps(poe)
uplink port: input port 1*10*100mbps
sfp: not support
extend: not support
network signal(transmission distance): ≤150M
working enviroment(working temperature): -10°_55°
material case: metal/pse output: 60w
power in: not support
size: 98*43*25mm



WWW.HIKANIRAN.COM



NETWORK SWITCH



HK-SW-P0402E

Poe Rj45 port: 4*10/100/mbps(poe)
 uplink port: 2*10/100mbps sfp:not support
 Bandwidth: 1.6 GBPS
 extend: not support
 network signal(transmission distance): ≤150M
 working enviroment(working temperature): -25°_55°
 material case: metal
 pse output: +52v 1.25a 65w
 power in: ac 110-240v 25-08
 size: 125*115*33mm



HK-SW-P0402

Poe Rj45 port: 4*10/100/mbps(poe)
 uplink port: 2*10/100mbps sfp:not support
 Bandwidth: 1.6 GBPS
 extend: not support
 network signal(transmission distance): ≤150M
 working enviroment(working temperature): -25°_55°
 material case: metal
 pse output: +52v 1.25a 65w
 power in: ac 110-240v 25-08
 size: 200*118*44mm



HK-SW-P0802E

Poe Rj45 port: 8*10/100/mbps(poe)
 uplink port: 2*10/100mbps sfp:not support
 Bandwidth: 1.6 GBPS
 extend: yes
 network signal(transmission distance): ≤150M
 working environment(working temperature): -25°_55°
 material case: metal
 pse output: +52v 2.3a 120w
 power in: ac 110-240v 25-03
 size: 200*118*44mm



HK-SW-P0802

Poe Rj45 port: 8*10/100/mbps(poe)
 uplink port: 2*10/100mbps sfp:not support
 Bandwidth: 1.6 GBPS
 extend: yes
 network signal(transmission distance): ≤150M
 working enviroment(working temperature): -25°_45°
 material case: metal
 pse output: +52v 2.8a 150w
 power in: ac 110-240v 25-03
 size: 200*118*44mm



HK-SW-P0802G

Poe Rj45 port: 8*10/100/mbps(poe)
 uplink port: 2*10/100/1000mbps sfp:not support
 Bandwidth: 12 GBPS
 extend: yes
 network signal(transmission distance): ≤150M
 working enviroment(working temperature): -25°_40°
 material case: metal
 pse output: +52v 2.3a 120w
 power in: ac 110-240v 25-04
 size: 200*118*44mm



HK-SW-P1602G-S1

Poe Rj45 port: 16*10/100/mbps
 uplink port: 2*10/100/1000mbps sfp: 1port
 Bandwidth: 12 GBPS
 extend: yes
 network signal(transmission distance): ≤150M
 working enviroment(working temperature): -25°_40°
 material case: metal
 pse output: +52v 4/8a 250w
 power in: ac 110-240v 25-03a
 size: 270*185*45mm



HK-SW-PG1602-S1

Poe Rj45 port: 16*10/100/mbps
 uplink port: 2*10/100/1000mbps sfp: 1port
 Bandwidth: 38 GBPS
 extend: not support
 network signal(transmission distance): ≤100M
 working enviroment(working temperature): -25°_40°
 material case: metal
 pse output: +52v 5/8a 300w
 power in: ac 110-240v 25-04
 size: 290*200*45mm



WWW.HIKANIRAN.COM



NETWORK SWITCH



HK-SW-P2402G-S1

Poe Rj45 port: 24*10/100/mbps
uplink port: 2*10/100mbps sfp:not support
Bandwidth: 12 GBPS
extend: not support
network signal(transmission distance): ≤150M
working enviroment(working temperature): -25°_40°
material case: metal
pse output: +52v 5.8a 300w
power in: ac 110-240v 25-01
size: 290*200*45mm



HK-SW-PG2402-S2

Poe Rj45 port: 24*10/100/1000/mbps
uplink port: 2*10/100/1000mbps sfp:not support
Bandwidth: 56 GBPS
extend: not support
network signal(transmission distance): ≤100M
working enviroment(working temperature): -20°_55°
material case: metal
pse output: +52v 5.8a 300w
power in: ac 110-240v 25-04
size: 330*210*44mm



WWW.HIKANIRAN.COM